



DESCRIPTION

The BAS16H is available in SOD-323 Package


FEATURES

- Small plastic SMD package.
- Continuous reverse voltage: max. 75V.
- High-speed switching in hybrid thick and thin-film circuits.
- RoHS Compliant
- Available in SOD-323 Package

ORDERING INFORMATION

| Package Type | Part Number |
|--|---------------|
| SOD-323 | BAS16H |
| Note | 3,000pcs/Reel |
| AiT provides all RoHS Compliant Products | |

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS

| | |
|--|--|
| V_R , Continuous Reverse Voltage | 75Vdc |
| I_F , Peak Forward Current | 200mAdc |
| $I_{FM(surge)}$, Peak Forward Surge Current | 500mAdc |
| P_D , Total Device Dissipation FR-5 Board ^{NOTE1} $T_A=25^\circ\text{C}$ | 200mW |
| Derate above 25°C | 1.57mW/ $^\circ\text{C}$ |
| $R_{\theta JA}$, Thermal Resistance Junction to Ambient | 635 $^\circ\text{C}/\text{W}$ |
| T_J, T_{STG} , Junction and Storage Temperature | -55 $^\circ\text{C}$ ~ +150 $^\circ\text{C}$ |

Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

NOTE1: FR-4 Minimum Pad



ELECTRICAL CHARACTERISTICS


T_A=25°C, unless otherwise noted

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|---------------------------------|-------------------|---|-----|-----|------|------|
| OFF CHARACTERISTICS | | | | | | |
| Reverse Voltage Leakage Current | I _R | V _R =75Vdc | | | 1.0 | uAdc |
| | | V _R =75Vdc, T _J =150°C | | | 50 | |
| | | V _R =25Vdc, T _J =150°C | | | 30 | |
| Reverse Breakdown Voltage | V _(BR) | I _{BR} = 100μAdc | 75 | | | Vdc |
| Forward Voltage | V _F | I _F =1.0mAdc | | | 715 | mV |
| | | I _F =10mAdc | | | 855 | |
| | | I _F =50mAdc | | | 1000 | |
| | | I _F =150mAdc | | | 1250 | |
| Diode Capacitance | C _D | V _R =0, f=1.0MHz | | | 2.0 | pF |
| Forward Recovery Voltage | V _{FR} | I _F =10mAdc, t _r =20ns | | | 1.75 | Vdc |
| Reverse Recovery Time | t _r | I _F =I _R =10mAdc, R _L =50Ω | | | 4.0 | ns |
| Stored Charge | Q _S | I _F =10mAdc to V _R =5.0Vdc, R _L =500Ω | | | 45 | pC |



TEST CIRCUIT

Figure 1. Recovery Time Equivalent Test Circuit



NOTE1: A 2.0kΩ variable resistor adjusted for a Forward Current (I_F) of 10mA.

NOTE2: Input pulse is adjusted so $I_{R(\text{peak})}$ is equal to 10mA.

NOTE3: $t_p \gg t_{rr}$



TYPICAL CHARACTERISTICS

Figure 1. Forward Voltage




Figure 2. Leakage Current






Figure 3. Capacitance





PACKAGE INFORMATION

Dimension in SOD-323 Package (Unit: mm)



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.80 | 1.00 | 0.031 | 0.040 |
| A1 | 0.00 | 0.10 | 0.000 | 0.004 |
| A3 | 0.15 REF | | 0.006 REF | |
| b | 0.25 | 0.40 | 0.010 | 0.016 |
| C | 0.089 | 0.177 | 0.003 | 0.007 |
| D | 1.60 | 1.80 | 0.062 | 0.070 |
| E | 1.15 | 1.35 | 0.045 | 0.053 |
| L | 0.08 | | 0.003 | |
| HE | 2.30 | 2.70 | 0.090 | 0.105 |



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.