



DESCRIPTION

The BAV99L is available in SOT-23 Package.



FEATURES

- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance
- Available in SOT-23 Package

ORDERING INFORMATION

Package Type	Part Number
SOT-23	BAV99L
Note	SPQ: 3,000pcs/Reel
AiT provides all RoHS Compliant Products	

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS

$T_A = 25^\circ\text{C}$

V_{RRM} , Repetitive Peak Reverse Voltage	70V
V_R , Continuous Reverse Voltage	70Vdc
I_F , Forward Current	215mAdc
$I_{F(AV)}$, Continuous Forward Current (Single Diode Loaded)	715mA
I_{FRM} , Repetitive Peak Forward Current	450mA
I_{FSM} , Non-Repetitive Peak Forward Surge Current	
$t = 1.0\mu\text{s}$	4.5A
$t = 1.0\text{ms}$	1.0A
$t = 1.0\text{s}$	0.5A
P_D , Power Dissipation	300mW
T_J , Junction Temperature	150°C
T_{STG} , Storage Temperature Range	-65°C ~+150°C

Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Max	Unit
Forward Voltage	V_F	$I_F = 1.0\text{mAdc}$	-	715	mVdc
		$I_F = 10\text{mAdc}$	-	855	
		$I_F = 50\text{mAdc}$	-	1000	
		$I_F = 150\text{mAdc}$	-	1250	
Reverse Current	I_R	$V_R = 70\text{Vdc}$	-	2.5	nA
		$V_R = 75\text{V}$	-	1	μA
		$V_R = 25\text{Vdc}, T_J = 150^\circ\text{C}$	-	30	
		$V_R = 70\text{V}, T_J = 150^\circ\text{C}$	-	50	
Diode Capacitance	C_D	$V_R = 0, f = 1.0\text{MHz}$	-	1.5	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 10\text{mAdc}, i_{R(REC)} = 1.0\text{mAdc}, R_L = 100\Omega$	-	6.0	ns
Forward Recovery Voltage	V_{FR}	$I_F = 10\text{mA}, t_r = 20\text{ns}$		1.75	V



TYPICAL CHARACTERISTICS

Figure 1. Forward Voltage




Figure 2. Leakage Current






Figure 3. Capacitance





PACKAGE INFORMATION

Dimension in SOT-23 Package (Unit: mm)



UNIT	A	B	b_p	C	D	E	H_E	A_1	L_p
mm	1.40	2.04	0.50	0.19	3.10	1.65	3.00	0.100	0.50
	0.95	1.78	0.35	0.08	2.70	1.20	2.20	0.013	0.20



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or server property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.