



DESCRIPTION

The SM712 transient voltage suppressor (TVS) diode is designed for asymmetrical (12V to 7V) protection in multi-point data transmission standard RS-485 applications. The SM712 may be used to protect devices from transient voltages resulting from electrostatic discharge (ESD), electrical fast transients (FET), and lightning.

The SM712 features 400 Watts ($t_p=8/20\mu s$) of power handling capability to accommodate the higher transient voltage levels which may be expected in extended common mode applications. This SM712 provides higher equipment reliability and eliminates the "guess work" required when using zener diodes that are not rated to handle such transient conditions. The integrated design aids in reducing voltage overshoot associated with trace inductance. The low clamping voltage of the SM712 minimizes the stress on the protected transceiver.

The SM712 is available in SOT-23 package

ORDERING INFORMATION

Package Type	Part Number
SOT-23	SM712
Note	SPQ: 3,000pcs/Reel

AiT provides all RoHS Compliant Products


FEATURES

- 400 watts peak pulse power ($t_p=8/20\mu s$)
- Transient protection for asymmetrical data lines to
 - IEC 61000-4-2 (ESD) $\pm 15kV$ (air), $\pm 8kV$ (contact)
 - IEC 61000-4-4 (FET) 40A (5/50ns)
 - IEC 61000-4-5 (Lightning) 12A (8/20 μs)
- Protects two +12V to -7V lines
- Low capacitance
- Low leakage current
- Low clamping voltage
- Solid-state silicon avalanche technology
- High temperature soldering guaranteed: $260^{\circ}C/10s$
- Available in SOT-23 package

APPLICATIONS

- Protection of RS-485 transceivers with extended
- Security systems
- Automatic Teller Machines (ATMs)
- Lighting Control – DALI
- Communication Equipments
- Fieldbus
- Modbus
- Profibus
- DMX512
- HFC systems
- Networks

PIN CONFIGURATION





ABSOLUTE MAXIMUM RATINGS

P _{PP} , Peak Pulse Power (8/20us)	400W
I _{PP} , Peak Pulse Current (8/20us)	17A
V _{ESD} , ESD per IEC 61000-4-2	Air ±15kV
	Contact ±8kV
T _{OPT} , Operating Temperature	-55°C~150°C
T _{STG} , Storage Temperature	-55°C~150°C

Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

T_{amb}=25°C

Parameter	Symbol	Conditions	Pin 1 or Pin 2 to Pin			Pin 3 to Pin 1 or Pin			Unit	
			3 (12V) TVS	Min.	Typ.	Max.	2 (7V) TVS	Min.		
Reverse Working Voltage	V _{RWM}	Pin 3 to 1 or Pin 2 to 1	-	-	-	12	-	-	7	V
Reverse Breakdown Voltage	V _{BR}	I _T = 1mA	13.3	-	-	-	7.5	-	-	V
Reverse Leakage Current	I _R	V _R = V _{RWM}	-	-	-	1	-	-	20	µA
Clamping Voltage 1	V _{C1}	I _{PP} = 5A, t _p = 8/20µs	-	-	-	20	-	-	12	V
Clamping Voltage 2	V _{C2}	I _{PP} = 17A, t _p = 8/20µs	-	-	-	26	-	-	16	V
Junction Capacitance 1	C _{J1}	V _R = 0V, f = 1MHz	-	-	-	75	-	-	75	pF
Junction Capacitance 2	C _{J2}	V _R = V _{RWM} , f = 1MHz	-	45	-	-	45	-	-	pF



TYPICAL CHARACTERISTICS

Figure 1. Non-Repetitive Peak Pulse Power vs.




Figure 2. Power Derating Curve




Figure 3. Pulse Waveform




Figure 4. Clamping Voltage vs. Peak Pulse Current






Figure 5. Capacitance vs. Reverse Voltage






DETAILED INFORMATION

Circuit Diagram




RS-485 Application Example





PACKAGE INFORMATION

Dimension in SOT-23 (Unit: mm)



Symbol	Min	Max
A	1.00	1.40
A1	-	0.10
b	0.35	0.50
c	0.10	0.20
D	2.70	3.10
E	1.40	1.60
E1	2.40	2.80
e	1.90 TYP	
L	0.10	0.30
L1	0.40	-
θ	0°	10°



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.