

**DESCRIPTION**

The AM029NS085HPJ is available in PDFN8(5x6) package.

VDSS	RDS(ON)	ID
85V	2.9mΩ	100A

**APPLICATIONS**


- Load Switch
- Motor Control and Drive
- Charge/Discharge for Battery Management System
- SMPS, Power Management

**ORDERING INFORMATION**

Package Type	Part Number	
PDFN8(5x6) SPQ: 5000pcs/Reels	PJ8	AM029NS085HPJ8VR
Note	V: Halogen free Package R: Tape & Reel	
AiT provides all RoHS products		

**FEATURE**

- 85V, 100A
- R<sub>DS(ON)</sub> Typ.= 2.9mΩ @ V<sub>GS</sub> = 10V
- Advanced Trench Technology
- Excellent R<sub>DS(ON)</sub> and Low Gate Charge
- 100% Avalanche Screened
- 100% ΔV<sub>ds</sub> Tested!

**PIN DESCRIPTION**

Pin #	Symbol	Function
1	S	Source
2	S	Source
3	S	Source
4	G	Gate
5	D	Drain
6	D	Drain
7	D	Drain
8	D	Drain

**ABSOLUTE MAXIMUM RATINGS**

T<sub>J</sub> = 25°C, unless otherwise specified.

V <sub>DS</sub> , Drain-to-Source Voltage	85V	
V <sub>GS</sub> , Gate Source Voltage	±20V	
I <sub>D</sub> , Continuous Drain Current	T <sub>C</sub> = 25°C	Package limit 100A Silicon limit 136A
	T <sub>C</sub> = 100°C	86A
I <sub>DM</sub> , Pulsed Drain Current <sup>(1)</sup>	400A	
E <sub>AS</sub> , Avalanche Energy, Single Pulse <sup>(2)</sup>	676mJ	
P <sub>D</sub> , Power Dissipation	T <sub>C</sub> = 25°C	114W
R <sub>θJC</sub> , Thermal Resistance, Junction-to-Case	1.1°C/W	
T <sub>STG</sub> , Storage Temperature Range	-55°C ~ +150°C	
T <sub>J</sub> , Junction Temperature Range	-55°C ~ +150°C	

1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.

2. EAS condition: Starting T<sub>J</sub>=25°C, L=0.5mH, I<sub>b</sub>=36A



**ELECTRICAL CHARACTERISTICS**

T<sub>J</sub> = 25°C, unless otherwise specified.

Parameter	Symbol	Conditions	Min	Typ.	Max	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	85	-	-	V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =80V, V <sub>GS</sub> =0V	-	-	1.0	μA
Gate-Body Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> = 20V, V <sub>DS</sub> =0V	-	-	100	nA
<b>On Characteristics</b>						
Gate Threshold Voltage	V <sub>GS(TH)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	2.0	3.0	4.0	V
Static Drain-Source ON-Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 70A	-	2.9	3.4	mΩ
Transconductance	g <sub>fs</sub>	V <sub>DS</sub> = 5V, I <sub>D</sub> = 50A		144		S
<b>Dynamic Characteristics</b>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 40V, V <sub>GS</sub> =0V, f=1.0MHZ	-	5621	-	pF
Output Capacitance	C <sub>oss</sub>		-	923	-	
Reverse Transfer Capacitance	C <sub>rss</sub>		-	10	-	
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> = 40V , I <sub>D</sub> =70A V <sub>GS</sub> =0V to 10V	-	85	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	35	-	
Gate Drain("Miller") Charge	Q <sub>gd</sub>		-	18	-	
Gate Plateau Voltage	V <sub>plateau</sub>			5.1		V
<b>Switching Characteristics</b>						
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> =40V, I <sub>D</sub> = 70A R <sub>GEN</sub> =3Ω, V <sub>GS</sub> = 10V	-	26	-	ns
Turn-On Rise Time	t <sub>r</sub>		-	67	-	
Turn-Off Delay Time	t <sub>d(off)</sub>		-	63	-	
Turn-Off Fall Time	t <sub>f</sub>		-	37	-	
<b>Drain-Source Diode Characteristics and Max Ratings</b>						
Maximum Continuous Drain to Source Diode Forward Current	I <sub>S</sub>	-	-	-	100	A
Maximum Pulsed Drain to Source Diode Forward Current	I <sub>SM</sub>		-	-	400	A
Drain to Source Diode Forward Voltage	V <sub>SD</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> = 30A	-	-	1.2	V
Reverse recovery time	t <sub>rr</sub>	I <sub>F</sub> = 70A	-	79	-	ns
Reverse recovery charge	Q <sub>rr</sub>	diF/dt=100A/μs	-	110	-	nC



## TYPICAL PERFORMANCE CHARACTERISTICS

Fig 1. Output Characteristics




Fig 2. Typical Transfer Characteristics




Fig 3. On resistance ( $R_{DS(on)}$ ) vs. Drain Current




Fig 4. On resistance ( $R_{DS(on)}$ ) vs. Gate Voltage




Fig 5. On resistance ( $R_{DS(on)}$ ) vs. Temperature




Fig 6. Capacitance Characteristics






Fig 7. Gate Charge Characteristics




Fig 8. Body-diode Forward Characteristics




Fig 9. Power De-rating




Fig 10. Current De-rating




Fig 11. Maximum Safe Operating Area




Fig 12. Max. Transient Thermal Impedance






Fig 13. Gate Charge Test Circuit




Fig 14. Resistive Switching Test Circuit & Waveform




Fig 15. Unclamped Inductive Switching Test Circuit & Waveform






Fig 16. Diode Recovery Test Circuit & Waveform





**PACKAGE INFORMATION**

Dimension in PDFN8(5x6) (Unit: mm)



Symbol	Millimeters	
	Min.	Max.
A	0.900	1.100
b	0.310	0.510
c	0.210	0.340
D	5.050	5.400
D1	4.950	5.150
D2	4.000	4.200
E	6.300	6.500
E1	5.750	5.950
E2	3.430	3.630
e	1.270 BSC.	
H	0.730	0.930
L	0.610	0.810
$\theta$	0°	12°



## **IMPORTANT NOTICE**

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc. integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or server property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.